# Compression Tools



C.A.T. AS SHOWN

## C.A.T. / C.A.T. AS / C.A.T. Multimedia Series

Connector Compression Tools

- Spring-loaded split jaw design allows for easy change out of connectors from most connector manufactur
- Durable cast aluminum body with clear visibility of the connector compression operation
- Simple tool calibration with supplied gauge block (*Not applicable to the FX models*)
- U.S. Patent Nos.: 5,934,137; 5,647,119 & 6,820,326

### C.A.T. / C.A.T. AS / C.A.T. Multimedia Series Ordering Guide

| MODEL | PART # | PLUNGER TIP | PLUNGER TIP COLOR | MATERIAL | CONNECTOR COMPATIBILITY | LENGTH | WEIGHT |
|---|---|---|---|---|---|---|---|
| Universal | 36175-1 | Interchangeable | Green | Black-Coated Cast Aluminum | *Refer to Chart Below* | 7.0" (178 mm) | 1.0 lb (454 |
| Universal FX | 37260 | Fixed / Non-Adjustable | | | | | |
| Universal EX | 36173 | Adjustable/Interchangeable | Black | | | | |
| Universal IEC/RCA-FX | 37765 | Fixed / Non-Adjustable | N/A | | | | |
| AS | 37720 | Adjustable/Interchangeable | Green | Black-Coated Cast Aluminum | *Two Jaw Sets for Added Versatility; Refer to Chart Below* | 7.4" (187 mm) | 1.1 lb (500 |
| AS-FX | 37835 | Fixed / Non-Adjustable | | | | | |
| AS-EX | 37780 | Adjustable/Interchangeable | Black | | | | |
| AS-DIGICON | 37785 | Adjustable/Interchangeable | Gray | | | | |
| AS-DIGICON-FX | 37845 | Fixed / Non-Adjustable | | | | | |
| AS-IEC/RCA-FX | 37830 | Fixed / Non-Adjustable | N/A | | | | |
| Multimedia | 38855 | Fixed / Non-Adjustable | Black | Red-Coated Cast Aluminum | *Refer to Chart Below* | 7.4" (187 mm) | 1.1 lb (500 |

### C.A.T. / C.A.T. AS / C.A.T. Multimedia Series Plunger Compatibility Guide

| CONNECTOR COMPATIBILITY | | | C.A.T. UNIVERSAL SERIES | | | | C.A.T. AS ALL SERIES | | | | | | C.A.T. MULTIM |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| TYPE | MANUFACTURER | NAME | UNIVERSAL | UNIVERSAL FX | EX | IEC/ RCA-FX | AS | AS-FX | AS-EX | AS-DIGICON | AS-DIGICON-FX | AS-IEC/ RCA-FX | |
| 59/6 | Arris-Digicon | DS & DT™ | • | • | | • | • | • | | • | • | • | • |
| | | DS RCA | | | | • | | | | | | • | • |
| | | DS RCA MINI / DS BNC | | | | | | | | | | | • |
| | Belden | SNAP-N-SEAL® | • | • | | • | • | • | | | | • | |
| | Corning Cabelcon | CX3 | • | • | | • | • | | | • | • | • | |
| | | CX3-IECF / CX3-IECM | | | | • | | | | | | • | |
| | Corning Gilbert | EFC / F-UE / F-UE-M | • | • | | • | • | • | | • | • | • | • |
| | | UltraRange® | • | • | | • | • | • | | • | • | • | • |
| | | UltraShield® | • | • | | • | • | • | | • | • | • | |
| | | RCA-UE / RCA-UE-M | | | | • | | | | | | | • |
| | | BNC-UE / BNC-UEM | | | | | | | | | | | • |
| | F-Conn | FS | • | • | | • | • | • | | • | • | • | • |
| | | FSC | | | | • | | | | | | • | • |
| | | FSU / FS-RCA / FSC-BNC | | | | | | | | | | | • |
| | Holland | SLC | • | • | | • | • | • | | • | • | • | |
| | PCT | DRS | • | • | | • | • | • | • | • | • | • | |
| | | DRS-IEF / DRS-IECFM | | | | • | | | | | | • | |
| | | TRS | | | • | | | | | | | | |
| | PPC | EX | | | • | | | | • | | | | |
| | | EX XL | • | • | | • | • | • | | • | • | • | |
| | | CMP | • | • | | • | • | • | | • | • | • | |
| | | CMP-MC | | | | | | | • | | | | |
| | | CMP-RCA / CMP-IEC | | | | • | | | | | | • | |
| | TFC | QCII | • | • | | • | • | • | | • | • | • | |
| 7 | Arris-Digicon | DS & DT™ | | | | | • | • | | • | • | • | |
| | Belden | SNAP-N-SEAL® | | | | | • | • | | | | • | |
| | Corning Gilbert | UltraSeal® | | | | | • | • | | | | • | |
| | PPC | EX | | | | | • | • | • | | | • | |
| | PCT | TRS | | | | | | | • | | | | |
| 11 | Arris-Digicon | DS & DT™ | | | | | | | | • | • | | |
| | Belden | SNAP-N-SEAL® | | | | | • | • | • | | | • | |
| | Corning Cabelcon | CX3 | | | | | • | • | • | | | • | |
| | Corning Gilbert | UltraRange®/ UltraSeal® / UltraSeal® 320 QR | | | | | • | • | • | | | • | |
| | | URS-MH | | | | | • | • | | • | • | • | |
| | PCT | DRS / DRS-320QR | | | | | • | • | • | • | • | • | |
| | PPC | EX / EX320QR | | | | | • | • | • | • | • | • | |
| | TFC | QCII | | | | | • | • | • | • | • | | |